

Betrieb von LED-Retrofit Lampen RaLED Star Standard RL-A mit verschiedenen Dimmern

Radium

Legende: green dimmability very good (under 25% light)
 yellow dimmable (under 40% light)
 red dimmability critical (flickering and/or sound possible, and/or only more than 40% light)
 white not tested



T: Trailing edge phase dimmer
 L: Leading edge phase dimmer
 U: Universal dimmer

Manufacturer	Dimmer-Type, Model	Mains/Power	Load Range [W]	Dimming Method	A60		A75		A100	
					1 Lamp	4 Lamps	1 Lamp	4 Lamps	1 Lamp	4 Lamps
Busch-Jaeger	6513 U-102	230/50Hz	420	T	100-0%	99-0%	100-18%	100-14%		
Busch-Jaeger	6523 U-102	230/50Hz	40-420	T	99-0%	99-0%	97-25%	98-20%		
Schneider	400GLI	230/50Hz	40-400	T	87-0%	90-0%	100-0%	100-0%		
ELKO	400GLI	230/50Hz			87-0%	90-0%	100-0%	100-0%		
Legrand	665114	230/50Hz	400	U	78-0%	82-0%	91-5%	91-5%		
Legrand	067083=048869=048869=048871=078407=	230/50Hz			78-0%	82-0%	91-5%	91-5%		
Bticino	L/N/NT4411NHC/HD/HS4411	230/50Hz			78-0%	82-0%	91-5%	91-5%		
Jung	225 NVDE	230/50Hz	20-500	L	88-0%	96-0%	100-7%	99-0%		
GIRA	226200	230/50Hz			88-0%	96-0%	100-7%	99-0%		
Siemens	5TC8 284	230/50Hz	20-525	T	99-0%	100-0%	100-16%	98-8%		
Gira	030700	230/50Hz	20-525	T	99-0%	100-0%	100-16%	100-13%		
Jung	225 TDE	230/50Hz			99-0%	100-0%	100-16%	100-13%		
ELKO	315GLE	230/50Hz	20-315	T	99-0%	100-0%	100-4%	100-3%		
Schneider	SBD315RC	230/50Hz			99-0%	100-0%	100-4%	100-3%		
Merten	MEG5136-0000	230/50Hz			99-0%	100-0%	100-4%	100-3%		
Osram	HTI DALI 315 DIM	230/50Hz	20-315	DALI-T	99-0%	100-0%	14-0%	13-0%		
Gira	117600	230/50Hz	50-420	U	97-0%	98-0%	0-0%	0-0%		
Jung	254 UDIE1	230/50Hz			97-0%	98-0%	0-0%	0-0%		
Merten	MEG5134-0000	230/50Hz			100-0%	100-0%	100-16%	100-15%		
Schneider	SBD200LED	230/50Hz	400		100-0%	100-0%	100-16%	100-15%		
Odace	S520512	230/50Hz			100-0%	100-0%	100-16%	100-15%		
Feller	40200.LEDxxx	230/50Hz			100-0%	100-0%	100-16%	100-15%		
Feller	40600 RLC	230/50Hz	20-600	U	94-0%	94-0%	99-10%	99-15%		
ELKO	600GLE/I	230/50Hz			94-0%	94-0%	99-10%	99-15%		
Merten	MEG5139-0000	230/50Hz			94-0%	94-0%	99-10%	99-15%		
Schneider	SBD600RCRL	230/50Hz			94-0%	94-0%	99-10%	99-15%		
ELKO	630GLE	230/50Hz	20-630	U	100-0%	100-0%	100-18%	100-14%		
Schneider	SBD630RC	230/50Hz			100-0%	100-0%	100-18%	100-14%		
Merten	MEG5137-0000	230/50Hz			100-0%	100-0%	100-18%	100-14%		
Feller	40600.RC	230/50Hz			100-0%	100-0%	100-18%	100-14%		
Berker	2861	230/50Hz	50-420	U	100-0%	100-0%	100-25%	100-24%		
DimMax	420 SL	230/50Hz	200	L/T	100-0%	100-0%	100-0%	100-0%		
Busch-Jaeger	2250 U	230/50Hz	60-600	L	63-0%	97-0%	61-4%	61-5%		
Legrand	770061	230/50Hz	400	RL	95-0%	95-0%	100-11%	100-11%		
Jung	1224 LEDUDE	230/50Hz		LED	100-0%	98-0%	100-0%	100-0%		
Gira	238500	230/50Hz			100-0%	98-0%	100-0%	100-0%		
ELKO	600GLI	230/50Hz	40-600	U	88-0%	92-0%	100-11%	100-0%		
Schneider	SBD600RL	230/50Hz			88-0%	92-0%	100-11%	100-0%		
Merten	MEG5133-0000	230/50Hz			88-0%	92-0%	100-11%	100-0%		
Feller	40600.RL	230/50Hz			88-0%	92-0%	100-11%	100-0%		
Odace	S520511	230/50Hz			88-0%	92-0%	100-11%	100-0%		
ELKO	420GLE/I	230/50Hz	40-420	U	80-0%	82-0%	100-8%	100-8%		
Schneider	SBD420RCRL	230/50Hz			80-0%	82-0%	100-8%	100-8%		
Merten	MEG5138-0000	230/50Hz			80-0%	82-0%	100-8%	100-8%		
Feller	40420.RLC	230/50Hz			80-0%	82-0%	100-8%	100-8%		
Odace	S520515	230/50Hz			80-0%	82-0%	100-8%	100-8%		
Hager	WUD87	230/50Hz	400	LED-U	100-0%	100-0%	100-17%	100-14%		
Altenburger	50,3	230/50Hz			99-0%	100-0%	100-16%	100-10%		
Merten	MEG 5170-0300	230/50Hz	10-200	U	100-0%	100-0%	100-0%	100-0%		
Schneider	5170	230/50Hz			100-0%	100-0%	100-0%	100-0%		
Busch-Jaeger	6526 U	230/50Hz			99-0%	97-0%	100-30%	100-32%		
Merten	MEG 5131	230/50Hz	40-400	L	88-0%	92-0%	98-0%	98-0%		
Schneider	SBD400RL	230/50Hz			88-0%	92-0%	98-0%	98-0%		
Merten	MEG 5132	230/50Hz			88-0%	92-0%	98-0%	98-0%		
PEHA	435 HAN	230/50Hz	60-600	L	83-0%	90-0%	68-0%	61-0%		
Merten	MEG 5140	230/50Hz	9-100	L	86-0%	94-0%	59-0%	68-0%		
Schneider	SBDSP1	230/50Hz			86-0%	94-0%	59-0%	68-0%		
Odace	S520518	230/50Hz			86-0%	94-0%	59-0%	68-0%		
Legrand	099314	230/50Hz	300	RL	93-0%	95-0%	100-0%	59-0%		
Legrand	770062	230/50Hz	400	RLC	99-0%	100-0%	100-0%	100-0%		
ABB	STD 50-3	230/50Hz	60-500	L	88-0%	91-0%	57-8%	57-7%		
Hamilton	KP1X40	230/50Hz	400		88-64%	98-67%	82-0%	57-0%		
ZANO	WH401	230/50Hz	400	L	90-0%	95-0%	68-0%	68-0%		
ZANO	WH251	230/50Hz	250		6-0%	96-0%	57-0%	57-0%		
VARILIGHT	HQ3W	230/50Hz	400		100-0%	100-0%	91-18%	93-18%		
VARILIGHT	JQP401W	230/50Hz	400	T	9-0%	99-0%	100-43%	100-41%		
AURORA	DSP 400	230/50Hz	400	L	9-0%	98-0%	0-0%	0-0%		
MK	K4501	230/50Hz	180	L	99-0%	100-0%	86-7%	86-7%		
CENTURY CONTROL	MULTI DIMMER	230/50Hz	60-600	U	94-0%	99-0%	100-0%	100-0%		
Legrand	078405	230/50Hz	600	RL	94-0%	96-0%	20-0%	100-0%		
Bticino	L/N/NT4408HC/HD/HS4408	230/50Hz			94-0%	96-0%	20-0%	100-0%		

Betrieb von LED-Retrofit Lampen RaLED Star Standard RL-A mit verschiedenen Dimmern

Radium

Legende:

green	dimmbility very good (under 25% light)
yellow	dimmbale (under 40% light)
red	dimmbility critical (flickering and/or sound possible, and/or only more than 40% light)
white	not tested



T: Trailing edge phase dimmer
L: Leading edge phase dimmer
U: Universal dimmer

Manufacturer	Dimmer-Type, Model	Mains/Power	Load Range [W]	Dimming Method	A60		A75		A100	
					1 Lamp	4 Lamps	1 Lamp	4 Lamps	1 Lamp	4 Lamps
ZANO	Z GRID 700	230/50Hz	250	LED	99-0%	100-0%	100-0%	100-0%		
ZANO	Z GRID 500	230/50Hz	500		99-0%	99-0%	100-0%	100-0%		
NEXUS	881P-01	230/50Hz	400	L	94-0%	97-0%	57-0%	57-0%		
bticino	NT4402N	230/50Hz	500	R	52-0%	52-0%	86-9%	86-11%		
Shuttle	SDIM-T-LED-500W	230/50Hz	2-500	T & LED-T	98-0%	98-0%	100-0%	100-8%		
VADSBO	LD 220	230/50Hz	1-200	U	98-0%	100-0%	100-2%	100-2%		
Merten	MEG 5135	230/50Hz	60-1000	L	98-0%	100-0%	100-0%	100-0%		
Schneider	ATTD1000RL	230/50Hz			98-0%	100-0%	100-0%	100-0%		
ELKO	1000LRI	230/50Hz			98-0%	100-0%	100-0%	100-0%		
Feller	31000	230/50Hz			98-0%	100-0%	100-0%	100-0%		
Siemens	5WG1-528-1AB31	230/50Hz	20-500	KNX-U	99-0%	99-0%	100-0%	100-0%		
Gira	217400	230/50Hz	4X20-250	KNX-U	98-0%	98-0%	100-0%	100-0%		
Jung	3904 REGHE	230/50Hz			98-0%	98-0%	100-0%	100-0%		
MASTER	DM-DGL	230/50Hz	1000	U / LED	99-0%	99-0%	100-2%	100-1%		
MASTER	DM-2500	230/50Hz	2500	U / LED	98-0%	98-0%	100-1%	100-1%		
DINUY	RE EL1 LE1	230/50Hz	400	LED	98-0%	99-0%	100-0%	100-11%		
Hugo Müller	paladin 872110 led	230/50Hz			98-0%	99-0%	100-0%	100-11%		
Eltako	EUD61NPN-UC	230/50Hz	5-400	R / L / C	100-0%	99-0%	100-0%	100-0%		
Vimar	20135	230/50Hz	3 - 100	U	100-0%	100-0%	100-0%	100-0%		
NIKO	310-0190001901	230/50Hz	5-200	U	98-0%	98-0%	100-1%	100-1%		
NIKO	330-0070000701	230/50Hz	5-200	U	98-0%	98-0%	100-0%	100-11%		

Typical values. Test performed with regarded lamps named. The test results reflect the measurement of the individual devices that were used in tests.

Radium does not take over any responsibility, warranty or liability that this results can also be achieved by using the devices under other conditions or when using successor models of the tested devices or different models of the same manufacturer. The test results were achieved by using the above mentioned LED-lamp types.

Radium does not take over any responsibility, warranty or liability that these results can also be achieved by using the devices under other conditions or when using other LED-lamp types.

Due to the big number of electronic components and many other influence factors noise can emerge in unfavourable conditons, which may be well audible in the case of resonance.

Generally speaking, employment of trailing edge dimmers is recommended. They require the neutral wire for installation.

Changes, errors and omissions excepted.