

Operation of LED-Retrofit Lamps LED Star Reflector AR111 G53 with various Dimmers



Legend:	green	dimmbility very good (under 25% light)
	yellow	dimmbable (under 40% light)
	red	dimmbility critical (flickering and/or noise possible, min. > 40% light)
	white	not tested



T: Trailing edge phase dimmer
L: Leading edge phase dimmer
U: Universal dimmer

AR111 75

43820777

43620778

Manufacturer	Dimmer-Type, Model	Mains/ Power	Load Range [W]	Dimming Method	1 Lamp	4 Lamps
ABB	STD 50-3	230/50Hz	60-500	L	70-7%	100-21%
Altenburger Electronic	50,3	230/50Hz			95-9%	100-12%
AURORA	DSP400	230/50Hz	400	T	63-0%	100-0%
Berker	2861	230/50Hz	50-420	U	92-12%	94-13%
Bticino	L/N/NT4411NHC/HD/HS4411	230/50Hz			75-1%	79-0%
bticino	NT4402N	230/50Hz	500	R		100-20%
Busch-Jaeger	6513 U-102	230/50Hz	420	T	100-25%	100-18%
Busch-Jaeger	6523 U-102	230/50Hz	40-420	T	81-0%	86-0%
Busch-Jaeger	2250 U	230/50Hz	60-600	L		
CENTURY CONTROL	MULTI DIMMER	230/50Hz	60-600	U	100-0%	100-0%
DimMax	420SL	230/50Hz	200	L/T	100-0%	100-0%
DINUY	RE EL1 LE1	230/50Hz	400	LED	100-0%	100-0%
ELKO	400GLI	230/50Hz			53-0%	95-0%
ELKO	315GLE	230/50Hz	20-315	T	90-0%	94-0%
ELKO	600GLE/I	230/50Hz			98-0%	100-0%
ELKO	600GLI	230/50Hz	40-600	U	70-9%	74-4%
ELKO	420GLE/I	230/50Hz	40-420	U	99-5%	100-2%
ELKO	1000LRI	230/50Hz				
ELKO	630GLE	230/50Hz	20-630	U	91-15%	94-14%
Eltako	EUD61NPN-UC	230/50Hz	5-400	R / L / C	91-0%	97-0%
Feller	40200.LEDxxx	230/50Hz			87-30%	93-9%
Feller	40600 RLC	230/50Hz	20-600	U	98-0%	100-0%
Feller	40600.RC	230/50Hz			91-15%	94-14%
Feller	40600.RL	230/50Hz			70-9%	74-4%
Feller	40420.RLC	230/50Hz			99-5%	100-2%
Feller	31000	230/50Hz				
Gira	226200	230/50Hz			69-0%	100-0%
Gira	030700	230/50Hz	20-525	T	91-10%	100-15%
Gira	117600	230/50Hz	50-420	U	95-12%	
Gira	217400	230/50Hz	4X20-250	KNX-U	97-0%	100-0%
Hager	WUD87	230/50Hz	400	LED-U	97-16%	100-16%
Hamilton	KP1X40	230/50Hz	400			100-15%
Hugo Müller	paladin 872110 led	230/50Hz			100-0%	100-0%
Jung	225 NVDE	230/50Hz	20-500	L	69-0%	100-0%
Jung	225 TDE	230/50Hz			91-10%	100-15%
Jung	254 UDIE1	230/50Hz			95-12%	
Jung	1224 LEDUCE	230/50Hz	3-100		95-0%	95-0%
Jung	3904 REGHE	230/50Hz			97-0%	100-0%
Legrand	665114	230/50Hz	400	U	70-1%	79-0%
Legrand	574319/574339	230/50Hz	400	U	70-1%	79-0%
Legrand	572239/572739	230/50Hz	400	U	70-1%	79-0%
Legrand	078407/079207	230/50Hz	400	U	70-1%	79-0%
Legrand	048869/048871	230/50Hz	400	U	70-1%	79-0%
Legrand	067083/048869	230/50Hz	400	U	70-1%	79-0%
Legrand	099314	230/50Hz	300	RL		
Legrand	770062	230/50Hz	400	RLC	89-2%	91-1%
MASTER	DM-DGL	230/50Hz	1000	U / LED	98-47%	
MASTER	DM-2500	230/50Hz	2500	U / LED	100-0%	100-0%
Merten	MEG5136-0000	230/50Hz			90-0%	94-0%
Merten	MEG5134-0000	230/50Hz			87-30%	93-3%
Merten	MEG5139-0000	230/50Hz			98-0%	100-0%
Merten	MEG5137-0000	230/50Hz			91-15%	94-14%
Merten	MEG5133-0000	230/50Hz			70-9%	74-4%
Merten	MEG5138-0000	230/50Hz			99-5%	100-2%
Merten	MEG 5170-0300	230/50Hz	10-200	U		

Operation of LED-Retrofit Lamps LED Star Reflector AR111 G53 with various Dimmers



Legend:	green	dimmmability very good (under 25% light)
	yellow	dimmmable (under 40% light)
	red	dimmmability critical (flickering and/or noise possible, min. > 40% light)
	white	not tested



T: Trailing edge phase dimmer
L: Leading edge phase dimmer
U: Universal dimmer

AR111 75

43820777

43620778

Manufacturer	Dimmer-Type, Model	Mains/ Power	Load Range [W]	Dimming Method	1 Lamp	4 Lamps
Merten	MEG 5131	230/50Hz	40-400	L	97-0%	100-0%
Merten	MEG 5132	230/50Hz			97-0%	100-0%
Merten	MEG 5140	230/50Hz	9-100	L		93-0%
Merten	MEG 5135	230/50Hz	60-1000	L		
MK	K4501	230/50Hz	180	L		93-0%
NEXUS	881P-01	230/50Hz	400	L	75-0%	100-0%
NIKO	310-0190001901	230/50Hz	5-200	U	100-0%	100-0%
NIKO	330-0070000701	230/50Hz	5-200	U	100-7%	100-6%
Odace	S520512	230/50Hz			87-30%	93-9%
Odace	S520511	230/50Hz			70-9%	74-4%
Odace	S520515	230/50Hz			99-5%	100-2%
Odace	S520518	230/50Hz				93-0%
Osram	HTI DALI 315 DIM	230/50Hz	20-315	DALI-T	100-6%	100-5%
PEHA	435 HAN	230/50Hz	60-600	L	54-0%	92-0%
Schneider	400GLI	230/50Hz	40-400	T	53-0%	92-0%
Schneider	SBD315RC	230/50Hz			90-0%	94-0%
Schneider	SBD200LED	230/50Hz	400		87-30%	93-3%
Schneider	SBD600RCRL	230/50Hz			98-0%	100-0%
Schneider	SBD630RC	230/50Hz			91-15%	94-14%
Schneider	SBD600RL	230/50Hz			70-9%	74-4%
Schneider	SBD420RCRL	230/50Hz			99-5%	100-2%
Schneider	5170	230/50Hz				
Schneider	SBD400RL	230/50Hz			97-0%	100-0%
Schneider	SBDSP	230/50Hz				93-0%
Schneider	ATTD1000RL	230/50Hz				
Shuttle	SDIM-T-LED-500W	230/50Hz	2-500	T & LED-T	97-0%	100-0%
Siemens	5TC8 284	230/50Hz	20-525	T	90-7%	90-16%
Siemens	5WG1-527-1AB31	230/50Hz	20-500	KNX-U	95-0%	100-0%
theben	DIMAX 544 plus P	230/50Hz	250	T	100-9%	100-11%
theben	DIMAX 534 plus	230/50Hz	400	T	100-2%	100-2%
VADSBO	LD 220	230/50Hz	1-200	U		
VARILIGHT	HQ3W	230/50Hz	400		89-2%	98-8%
VARILIGHT	JQP401W	230/50Hz	400	T		
Vimar	20135	230/50Hz	3 - 100	U		
ZANO	WH401	230/50Hz	400	L	72-0%	100-0%
ZANO	WH251	230/50Hz	250		71-0%	100-0%

Tests have been carried out with HTM70 transformer. The test results reflect the measurement of the individual devices that were used in tests.

Radium does not take over any responsibility, warranty or liability that this results can also be achieved by using the devices under other conditions or when using successor models of the tested devices or different models of the same manufacturer.

The test results were achieved by using the above mentioned LED-lamp types.

Radium does not take over any responsibility, warranty or liability that these results can also be achieved by using the devices under other conditions or when using other LED-lamp types. Installation and operational notes are to be observed.

Due to the big number of electronic components and many other influence factors noise can emerge in unfavourable condiditons, which may be well audible in the case of resonance.

Generally speaking, employment of trailing edge dimmers is recommended. They require the neutral wire for installation.

Changes, errors and omissions excepted.