



Radium
Die Lichtmarke

Now available: 24V DALI Drivers

Product features:

- 24V DALI DT6 and DT8 Driver for LED modules
- DALI2
- Flickerfree according to IEEE1789 standard
- 50,000 h service life
- Installer-friendly, spacious housing
- Good strain relief
- Suitable for indoor applications (IP20)
- Controllable with conventional wall switches
- Multi channel driver, additionally controllable via DMX
- suitable for PushDIM



1



2



3



°C



max. °C



l (mm) w (mm) h (mm)



DT



pcs.

Dimmable LED Driver, DALI



220...240



50/60



24 DC

One channel

1	OTDA4070	DRIVER DALI 1CH 36W/24V IP20	-20...+50	-20...+90	210	43	30	DT6	50
2	OTDA4071	DRIVER DALI 1CH 75W/24V IP20	-20...+50	-20...+80	293	43	30	DT6	30
2	OTDA4072	DRIVER DALI 1CH 100W/24V IP20	-20...+50	-20...+80	293	43	30	DT6	30
3	OTDA4073	DRIVER DALI 1CH 150W/24V IP20	-20...+50	-20...+85	352	43	30	DT6	20

Multi channel

2	OTDA4074	DRIVER DALI 2CH 75W/24V IP20	-20...+50	-20...+80	293	43	30	DT8	30
3	OTDA4075	DRIVER DALI 2CH 150W/24V IP20	-20...+50	-20...+85	352	43	30	DT8	20
3	OTDA4076	DRIVER DALI/DMX 4CH 150W/24V IP20	-20...+50	-20...+85	352	43	30	DT6	20