
Technical Information

XERADEX L40/175SB-AZ48/93

Revision: 1.3 - 02/2020 Supersedes: 1.2 - -08/18 Status: valid

Data Sheet




RADIUM XERADEX® VUV excimer lamps offer an exceptionally high VUV efficiency. XERADEX® lamps are the high-tech solution for cost effective surface cleaning/activation, purification or etching.

Electrical data

Rated power 20 W

Spectral data

Peak wavelength 172 nm Radiation intensity at lamp surface 35 mW/cm² Generates ozone yes



Operating conditions

| Burning position | any |
|--|--------------|
| Cooling | not required |
| Electronic control gear (power supply) | DBD 20 |

Lifespan

Recommended service life 2500 h Radiation flux after 2500h >70%

For complete operating, design-in, transportation and storage guidelines, please kindly refer to the Radium XERADEX® Application Notes.

Radium Lampenwerk Wipperfuerth Dr.-Eugen-Kersting-Strasse 6 D-51688 Wipperfürth · Germany Phone +49 (0)2267 81-398 Fax +49 (0)2267 81-503

Email: xeradex@radium.de
Web: www.tech.radium.de

Dimensions

RAD code 34317665

Applications

- Surface treatment
 - Removal of organic residue, resist
 - Cleaning of photomasks
 - Etching of plastic surfaces
- Activation of surface bonds
 - Improved deposition (photoresist, detergents)
 - Adjustment of contact angle
- Photo induced processes
 - Matting of lacquer
 - Ozone production
 - UV/ozone cleaning without external ozoniser

Advice

- Lamp emits high-energy UV radiation, which is readily absorbed by oxygen under generation of ozone.
- Provide ample ventilation and operate the lamp in suitable environment only.
- Lamp is designed for operation with matching power supply. Do not connect to any other power supply.
- Lamp is operated at high voltage. Lamp may only be installed, exchanged and operated by qualified personnel.















